



## CCITT G.703 Krone IDC Balun



Part Number	Description
-------------	-------------

See Configuration chart

CCITT G.703 Krone IDC Balun

### CCITT G.703 Krone IDC types:

BNC male



BNC female bulkhead with plastic thread



1.6/5.6 male



1.6/5.6 female bulkhead



BT43 male floating mount



BT43 female



1.0/2.3 female bulkhead



These **CCITT G.703 Krone IDC baluns** for panel mounting can be supplied with a variety of coaxial connectors BNC, 1.6/5.6, BT43, 1.0/2.3.  
Twisted pair termination via 3 pole Krone IDC

- No AC power or batteries needed
- Link-to-data isolation: Mini. 250V
- Bi-directional signal conversion
- Operating temperature: 0-75°
- Ultra-miniature enclosure
- Typical distance on good quality cable will be 180 meters

## Technical Specification

<b>2-8 Mbit/s speed version for E1 (T1), E2 (T2) data streams</b>	Impedance: 75 ohm to 120 ohm/100 ohm Insertion loss: Max. 0.2dB (2Mbps); Max. 0.3dB (8Mbps) Return loss: -29dB(2Mbps); -21dB(8Mbps) Cross talk: better than -80dB from 0.1 to 12MHz between any 2 baluns mounted distance up to 15mm
<b>2-8-34 Mbit/s speed version for E1 (T1) to E3 (T3) data streams</b>	Impedance: 75 ohm to 120 ohm/100 ohm Insertion loss: Max. 0.3dB (8Mbps); Max. 0.9dB from 0.2-70MHz Return loss: -21B(8Mbs); -15dB from 1 to 70 MHz Cross talk: better than -60dB from 1MHz to 70MHz between any 2 baluns mounted distance up to 15mm
<b>34 to 155 Mbit/s speed version for E3 (T3) and higher data streams</b>	Impedance: 75 ohm to 120 ohm/100 ohm Insertion loss: Max. 0.8dB from 860 KHz to 52 MHZ Max. 1.5dB from 50KHz to 240 MHz Return loss: Max. 15dB from 1MHz to 240 MHz Cross talk: -80dB from 1MHz to 240MHz between any 2 baluns mounted distance up to 15mm

## Order Configuration chart

BL-134 XX 1 X X X

